

People Counter Specifications

	PT Counter Series	Micro Counter Series
Models	Display (PRxD) Wireless (PRxW) USB (PRxU)	Display (MRx11D) Wireless (MRx11W)
Counting Method	Bi-Directional (PRx_20): separate count for in/out Non-Directional (PRx_10)	Non-Directional (MRx11)
Dimensions	116 x 69 x 22 mm (approx)	85 x 53 x 16 mm (approx)
Power Supply	2 x 1.5V AA	1 x 3V Lithium (CR2450)
Battery Life	1 Year (approx)	1 Year (approx)
Maximum Counting Distance	Up to 6 m (unobstructed) Ideal within 4 m	Up to 5 m (unobstructed) Ideal within 3.5 m
Mounting Style	Side & Rear	Rear
Counting Beam	Front	Side
Weather Proof Casing	Optional on Display & Wireless Models	-
Mounting Bracket	Rear Mounting Plate Optional Right Angle Bracket	Double Side Adhesive Strip (Included)
Included Software	SensorServer Application for Windows inc. Reports and CSV export (Wireless & USB Models Only)	SensorServer Application for Windows inc. Reports and CSV export (Wireless & USB Models Only)
Wireless Frequency	915 MHz 868 MHz optional (Wireless Model Only)	915 MHz 868 MHz optional (Wireless Model Only)
Wireless Range to Sensor Network Gateway (SNG)	Up to 20 to 30 metres (Wireless Model Only) <i>Note: SNG requires AC power and RJ45 ethernet connectivity to network</i>	Up to 20 to 30 metres (Wireless Model Only) <i>Note: SNG requires AC power and RJ45 ethernet connectivity to network</i>



Side view of PT Counter (top)
compared with Micro Counter



Top view of iPhone 5 (left) compared with
PT Counter (middle) and Micro Counter



Flat/rear mount of Micro Counter (top) compared
with side mount of PT Counter on door frame

For more information visit www.evolveplus.com.au